


LED-STRIP SOB 320 • 48V • 12W • 6500K • IP20 • 1680LM • RA92 • 8MM



12W/m
SOB/SMD technology – uniform light line
up to 135 lm/W
8mm PCB 2oz R2R
48V DC
2.5 cm cutting section
Ra > 90
75000h L70 lifetime
3M 300 LSE adhesive tape
5-year warranty

A professional next-generation LED-strip designed for continuous operation, offering luminous efficacy up to 135 lm/W. The SOB/SMD technology is an enhanced alternative to traditional COB strips – combining the uniform, seamless light line typical of COB with the higher durability and efficiency of SMD diodes. A special silicone layer

further smooths the light and increases mechanical resistance, eliminating common weaknesses of COB tapes. The 320 precisely placed LEDs ensure exceptional uniformity, high colour rendering and very low SDCM values for perfect colour consistency along the entire length. The strip features a wide 160°+ beam angle, an ultra-short 2.5 cm cutting module and strong 3M 300 LSE adhesive for secure installation. An ideal choice for premium installations where quality, aesthetics and reliability matter.

Specification

Parameter	Value
Symbol	SOB-12-CW-48
EAN13	5901289757652
ETIM CLASS	Light ribbon-/hose/-strip
Socket	wires
Model	Tape
Mains or non-mains	NMLS
Dimmable	yes
Power [W]	12
Power for white light [W]	12
Colour of light	White
Number of nodes per meter	320
Degree of protection	IP20
Suitable for use	
cutting length [cm]	2.5
Voltage [V]	48
Voltage type	DC
Colour temperature [K]	6500
Colour rendering index CRI	92
Minimal colour rendering index	90
Maximal colour rendering index	93
Colour rendering index R9	72
Energy efficiency class	E
Luminous flux [lm]	1680
Luminous flux - white light [lm]	1680
Beam angle [°]	160
Correspondence beam angle	Sphere 360°
Non-directional or directional light source	Non-directional light source NDLS
Survival factor	0.9
Lumen maintenance factor	0.96
Chromaticity coordinates - x	0.31
Chromaticity coordinates - y	0.335
With Self-adhesive	yes
Equivalent power [W]	108
The energy consumption - white light [kW/1000h]	12
Min. number of switching cycles	75000
Rated life time L70/B50 at 25 °C [h]	75000
Colour-tuneable light source (CTLS)	no
Connected light source (CLS)	no
High-luminance light source (HLLS)	no
Anti-glare shield	no



Operating temperature [°C]	-20 ~ 45
Colour consistency in McAdam ellipses	3
Length [mm]	1000
Width [mm]	8
Height/depth [mm]	3
Weight [kg]	0.036

